



ACCOLADE PLUS

PUR reinforced homogeneous sheet / Manufactured in Australia



- Exclusive homogeneous formulation including replenishing polyurethane throughout the thickness of the floor.
- Protective polyurethane finish reduces initial and ongoing maintenance and increases scuff resistance.
- The embossed surface texture and highly accented jaspe (multi-color chip) visual help hide dirt and wear patterns created in high traffic areas.
- 24 colors styled to facilitate multiple color combinations within the product collection.
- Excellent durability, maintainability & resilience and resistance to indentation, rolling loads, dirt and static loads.
- Applications: healthcare, education, office and hospitality.



TECHNICAL INFORMATION

Requirement	Type of floor covering Pattern PUR through the mix Fire resistance Slip - Oil-wet ramp	Homogeneous sheet with polyurethane reinforced Embossed surface/accented jaspe/non directional ISO 9239-1 Critical radiant flux Smoke development rate AS/NZS 4586 Appendix A – Wet pendulum Appendix D – Oil-wet ramp	Yes > 11 kW/m ² < 750 % minute Y R9
General Properties	Roll width Roll length Coverage Overall gauge Wear layer Product weight Abrasion / volume loss Residual Indentation Curling after heat Flexibility Seam strength Color fastness Static load limit	EN 426 EN 426 EN 428 EN 429 EN 430 EN 660-2 EN 433 EN 434 EN 435 Test A EN 684 ISO 105-B02 (method 3) ASTM F970 (modified)	1.83 m 16 m 29,3 m ² 2.0 mm 2.0 mm 3,100 g/m ² group P ≤ 0.10 mm ≤ 8 mm 20 mm mandrel, no crack mean ≥ 240 N/50 mm ≥ 6 750 psi (52.73 kg/cm ²)
Classification	Commercial Industrial	EN 685 EN 685	34 very heavy 43 heavy

