



ACCOLADE PLUS ^{PUR²}

R10 X SLIP RESISTANCE
(2mm gauge x 1.83m x 16m sheet)

ACCOLADE SAFE

R10 B W SLIP RESISTANCE
(2mm gauge x 1.83m x 16m sheet)



SPICE WHITE



CAPPUCCINO



IRONBARK




WHITEHAVEN



DARLING GREY



MURRAY CLAY



CEDUNA WHITE




SAND GREY



BLACK OPAL




STERLING GREY




NAPIER GREY




BLACK ROCK




BONDI SAND




CAPRICORN BEIGE



CITRUS YELLOW



KALGOORLIE GOLD




CARNARVON RED




BYRON BLUE




BELLS BLUE



SORRENTO BLUE



WHITSUNDAY BLUE



LEMONGRASS



DAINTREE GREEN

ACCOLADE PLUS ACCOLADE SAFE WALLFLEX

COMMERCIAL FLOORING
& WALLING - VINYL SHEET





VINYL SHEET / Vinyl Tile / Linoleum


Variations may occur between photographic images, samples and batches in terms of colour, shade, pattern or similar.

- | | | | |
|---------------------|---|--|---|
| Practical | <ul style="list-style-type: none"> Exclusive homogeneous formulation including replenishing polyurethane throughout the thickness of the floor. Protective polyurethane finish reduces initial and ongoing maintenance and increases scuff resistance. | <ul style="list-style-type: none"> A 'safety floor' without impregnated silicon carbide chips that attract and hold dirt and increase the maintenance effort and wear and tear on cleaning equipment. | <ul style="list-style-type: none"> Polyurethane coating aids maintenance. Clean, simple design for an uncomplicated look or the addition of a frieze if desired. 1.5 metre width ideal dado height for ease of installation. |
| Durable | <ul style="list-style-type: none"> Homogeneous construction for excellent dent and gouge resistance. The embossed surface texture and highly accented jaspe (multi-colour chip) visual help hide dirt and wear patterns created in high traffic conditions. | <ul style="list-style-type: none"> The embossed surface reduces aquaplaning, while aiding slip resistance. | <ul style="list-style-type: none"> Polyurethane coating reduces maintenance costs and protects long term appearance. Homogeneous construction for excellent dent and gouge resistance. |
| Applications | <ul style="list-style-type: none"> Hospital Aged Care Health Care Education Light Industrial Mercantile Hospitality | <ul style="list-style-type: none"> Hospital Aged Care Health Care Education Light Industrial Mercantile Hospitality | <ul style="list-style-type: none"> Hospital Aged Care Health Care Education Light Industrial Mercantile Hospitality |

TECHNICAL DATA

| | ACCOLADE PLUS | ACCOLADE SAFE | WALLFLEX |
|--|---------------|--|--|
| Type of floor covering/wall covering | EN 649 | Homogeneous sheet vinyl | Homogeneous sheet vinyl |
| Manufactured in | Australia | Australia | Australia |
| Overall thickness | EN 428 | 2.0mm | 2.0mm |
| Wear layer thickness | EN 429 | 2.0mm | 2.0mm |
| Roll dimensions | EN 426 | 1.83m x 16m | 1.83m x 16m |
| Polyurethane reinforced | | Yes PUR ² | No |
| Wear resistance | EN 660-2 | Group P | Group M |
| Best Practice PVC (GBCA guidelines) | | Yes | Yes |
| LOW TVOC | | ≤150µg/m ² /hr (GBCA limit < 500µg/m ² /hr) | ≤150µg/m ² /hr (GBCA limit < 500µg/m ² /hr) |
| TVOC Emissions | EN 13419-1 | | |
| Slip resistance | AS/NZS 4586 | | |
| Appendix A: Wet pendulum | | X* | W* |
| Appendix C: Wet/barefoot ramp | | | B* |
| Appendix D: Oil-wet ramp | | R10* | R10* |
| *CSIRO Tested, for detail refer to individual Test Reports | | | |
| Fire resistance | ISO 9239-1 | | |
| Critical radiant flux | | > 11 kW/m ² | > 11 kW/m ² |
| Smoke development rate | | < 750% minutes | < 750% minutes |
| Fire resistance | AS/NZS 3837 | | |
| Cone Calorimeter | | Group 3 | N/A |
| Ave. specific extinction area | | <250m ² /kg | <250m ² /kg |
| Classification | EN 685 | Commercial: 34  Industrial: 43  | Commercial: 34  Industrial: 43  |


Visit www.armstrongflooring.com.au or contact **Customer Service 1800 632 624** for technical data, installation, cleaning and maintenance instructions.



ACCOLADE PLUS ACCENTS

 SLIP RESISTANCE


(2mm gauge x 1.83m x 16m sheet)




MANDARINE




SOFT SUN



BANKSIA RED



MISTY BLUE




LEAF GREEN




WALLFLEX


(1.25mm gauge x 1.5m x 20m sheet)




DOVE WHITE




BLUE HARMONY




ACID GREEN




NEUTRAL WHITE




ICE WHITE




LINEN



COOL WHITE



BLUE GREY



MUSHROOM

Variations may occur between photographic images, samples and batches in terms of colour, shade, pattern or similar.

