



# CERAMAGUARD®/ CERAMAGUARD FINE FISSURED™

Square Lay-in  
smooth texture

UP TO **38%** RECYCLED CONTENT

**LEED®**

acoustics

energy

daylight & views

indoor air quality

renewable materials

recycled content


waste mgmt

local\* materials

Calculate LEED contribution at [armstrong.com/greengenie](http://armstrong.com/greengenie)  
\*LOCATION DEPENDENT

**10-YEAR Availability**

Items  
605  
607  
608



Ceramaguard with Prelude Plus XL Fire Guard 15/16" suspension system (Pg. 258)

## KEY SELECTION ATTRIBUTES

- Inorganic product. Resistant to the growth of mold, mildew, and bacteria.
- Durable – Washable, Scrubbable, Soil-resistant
- Resistance to chemical fumes
- Non-directional visual reduces installation time and scrap
- Superior resistance to sagging in high humidity conditions including standing water and outdoor applications
- 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth

## TYPICAL APPLICATIONS

- Laboratories
- Locker rooms/indoor pools
- Hydrotherapy/shower areas
- Food preparation areas (unperforated only)
- Exterior soffits/canopies
- Indoor parking garages
- Marine use (See note under "Application Considerations")

## COLOR



White

## VISUAL SELECTION

## PERFORMANCE

Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 <a href="http://armstrong.com/catdws">armstrong.com/catdws</a>	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability			Recycled Content	Recycle Program	Warranty*			
				NRC	CAC						Wash	Scrub	Soil						
<b>CERAMAGUARD* - UNPERFORATED</b>																			
15/16" Square Lay-in	1	<b>605</b>	24 x 48 x 5/8"	□	UL Classified	N/A	40	Fire Guard	0.88	•	•	•	•	•	•	•	Std	-	30
<b>CERAMAGUARD FINE FISSURED - PERFORATED</b>																			
15/16" Square Lay-in	1	<b>607</b>	24 x 24 x 5/8"	□	0.55	38	Fire Guard	0.82	•	•	•	•	•	•	•	•	Std	-	30
	1	<b>608</b>	24 x 48 x 5/8"	□	0.55	40	Fire Guard	0.82	•	•	•	•	•	•	•	•	Std	-	30

\* Plain pattern (unperforated) is not appropriate where aesthetics or visual consistency is important.

## SUSPENSION SYSTEMS

15/16"



Prelude®, Prelude Plus XL® Aluminum, Prelude XL Fire Guard, Prelude Plus XL Fire Guard, Prelude Plus XL Stainless Steel, Prelude XL for Exterior Applications

## PHYSICAL DATA

### Material

Ceramic and mineral fiber composite

### Surface Finish

Scrubable factory-applied plastic paint finish

### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard™: A fire resistive ceiling when used in applicable UL assemblies

### ASTM E1264 Classification

Type XX (high density ceramic-like composition with scrubable finish). Pattern C E (items 607, 608); Pattern G (item 605) Fire Class A



### Sag Resistance

HumiGuard® Max – superior resistance to sagging in high humidity conditions including standing water and outdoor applications.

### Anti Mold/Mildew & Bacteria

Totally inorganic product. Resistant to the growth of mold, mildew, and bacteria.

### VOC Emissions

Third party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

### Insulation Value

R Factor — 1.4 (BTU units)  
R Factor — 0.25 (Watts units)

### Application Considerations

For outdoor soffits and canopies, wind uplift should be considered. Ceramaguard is non-combustible per ASTM E136 and ISO 1182. See USCG Approval 164.109/52/0 for marine applications in all waters.

### 30-Year Performance Guarantee & Warranty†

When installed with Armstrong Suspension System. Details at [armstrong.com/warranty](http://armstrong.com/warranty)

### Weight: Square Feet/ Carton

605, 608 – 1.52 lbs/SF; 48 SF/ctn  
607 – 1.48 lbs/SF; 48 SF/ctn

### Minimum Order Quantity

1 carton

### Metric Items Available

605M, 607M, and 608M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine™ / 1 877 ARMSTRONG  
[armstrong.com/commceilings](http://armstrong.com/commceilings)  
(search: ceramaguard)  
BPCS-3224-413

LEED® is a registered trademark of the U.S. Green Building Council  
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates © 2013 AWI Licensing Company  
Printed in the United States of America

