

# CIRRUS® Open Plan

Square Lay-in & Tegular

fine texture



Cirrus Open Plan with Silhouette® 9/16" Bolt-Slot 1/4" reveal grid (Pg. 217); Axiom® Classic Trim (Pg. 236)

## Key Selection Attributes

- Excellent solution in mixed (open plan/closed plan) office design
- Excellent combination of acoustical performance; Articulation Class (170), NRC (0.75) and CAC (35)
- 30-Year Limited System Warranty against visible sag (excludes items 551, 565, 568), mold/mildew, and bacterial growth

## Typical Applications


- Open plan and closed offices
- Healthcare – assists in addressing HIPAA and FGI acoustical requirements
- Libraries/media centers
- Lobbies/reception areas
- Computer rooms

**Detail** (Other Suspension Systems compatible. Refer to listing on page 142.)

**Color**



Cirrus Open Plan  
Beveled Tegular



Cirrus Open Plan with  
Silhouette 9/16"  
Bolt-Slot 1/4" reveal grid



White (WH)

# CIRRUS® Open Plan

## Square Lay-in & Tegular

fine texture

Recycled Content: **66%**

armstrong.com/greengenie

### LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
✓	✓	✓	✓	✓	✓

Location Dependent

### LEED for Schools

Acoustics	Low Emitting or CHPS
✓	✓

\$\$\$\$\$




### Visual Selection

### Performance Selection

Dots represent highest level of performance.

Edge Profile	Suspension Detail Dwg. Pgs. 226-228	Item No.	Dimensions	UL Classified			Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	Durable	Recycle Program	
				Acoustics NRC	CAC	AC							
<b>CIRRUS Open Plan</b>													
9/16" Beveled Tegular	31-34, 54	<b>558</b> <b>558M</b>	2' x 2' x 7/8" 600 x 600 x 22mm	□	0.75	35	170	Class A	0.85	HumiGuard+	BioBlock+	Standard	Yes
	31-34, 54	<b>568</b> <b>568M</b>	2' x 4' x 7/8" 600 x 1200 x 22mm	▭	0.75	35	170	Class A	0.85	Standard	•	Standard	•
15/16" Angled Tegular	7	<b>556</b> <b>556M</b>	2' x 2' x 7/8" 600 x 600 x 22mm	□	0.75	35	170	Class A	0.85	•	•	Standard	•
	7	<b>551</b> <b>551M</b>	2' x 4' x 7/8" 600 x 1200 x 22mm	▭	0.75	35	170	Class A	0.85	Standard	•	Standard	•
15/16" Square Lay-in	1	<b>563</b> <b>563M</b>	2' x 2' x 7/8" 600 x 600 x 22mm	□	0.75	35	170	Class A	0.85	•	•	Standard	•
	1	<b>565</b> <b>565M</b>	2' x 4' x 7/8" 600 x 1200 x 22mm	▭	0.75	35	170	Class A	0.85	Standard	•	Standard	•

### Suspension Systems



### Physical Data

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

**ASTM E1264 Classification**  
Type III, Form 1, Pattern E I C  
Fire Class A

**Sag Resistance**  
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

**VOC/Formaldehyde Emissions**  
Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions and is listed on CHPS High Performance Products Database for Low-Emitting Materials.

**Anti Mold/Mildew & Bacteria**  
BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

**Insulation Value**  
R Factor – 2.3 (BTU units)  
R Factor – 0.40 (Watts units)

**30-Year Performance Guarantee & Warranty Information**  
See warranty details in the back of this catalog

**Application Considerations**  
Not recommended for rooms containing MRI equipment

**Weight; Square Feet/Carton**  
551, 565, 568 – 1.21 lbs/SF; 48 SF/ctn  
556, 558 – 1.40 lbs/SF; 40 SF/ctn  
563 – 1.33 lbs/SF; 40 SF/ctn