



altro

the future is safer with altro



EN14041  
0120  
GB06/72664



Manufactured by:  
Altro Ltd, Works Road  
Letchworth Garden City  
SG6 1NW  
United Kingdom

## Altro Suprema™ II

Altro Suprema™ II Impermeable PVC safety floor featuring Altro Easyclean Maxis PUR™, for improved cleanability and an integral bacteriostat, to ensure hygiene and a permanent anti-bacterial performance. Contains bio-plasticiser - a renewable resource. [www.altro.com](http://www.altro.com)

Altro Suprema™ II Suelo de Seguridad de PVC impermeable Altro Easyclean Maxis PUR™, para una mayor facilidad de limpieza. Contiene un bacteriostato en toda la masa. Con todo ello garantiza un óptimo comportamiento higiénico y antibactericida. Contiene bio-plasticadores, un recurso renovable. [www.altroscandess.es](http://www.altroscandess.es)

Altro Suprema™ II Undurchlässiger PVC Sicherheitsbodenbelag mit Altro Easyclean Maxis PUR™ Vergütung, für verbesserte Reinigung sowie integriertem Bakteriostat, für permanente Hygiene und antibakterielle Wirkung. Enthält Bio-Weichmacher – ein erneuerbarer Wertstoff. [www.altro.de](http://www.altro.de)

Colours Colores Farben	40		
Flooring Type Tipo de pavimento Belagsart		EN 13845/ EN 13553	Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag
Classification for use Areas de uso Einsatzbereiche		EN 685	34 & 43 34 y 43 34 & 43
Slip Resistance Resistencia al deslizamiento Rutschsicherheit		TRRL EN 13845 EN 13893 DIN 51130	≥ 36 Esf DS R10
Thickness Espesor Total Gesamtdicke		EN 428	2 mm
Wear Layer Capa de uso Nutzschicht		EN 429	0.8 mm
Flexibility Flexibilidad Flexibilität		EN 435	Pass Conforme bestanden
Weight Peso Flächengewicht		EN 430	2.6 kg/m <sup>2</sup>
Roll Dimensions Dimensiones del rollo Rollenabmessungen		EN 426	2.0m x 20.00m - 40m <sup>2</sup>
Light Fastness Resistencia a la luz Lichtechtheit		EN 20105-B02	≥ 6
Sound Insulation Aislamiento acústico Trittschal		ISO 140-8	5 dB
Wear Resistance Abrasión Verschleißverhalten		EN 13845	≤10% particles lost over 50000 Cycles ≤10% de las partículas perdidas en 50.000 ciclos ≤10% Partikel werden über 50000 Umdrehungen verloren
Indentation Punzonamiento Resteindruck		EN 433	≤ 0.10mm
Fire Performance Reacción al fuego Brandverhalten		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥8kW/m <sup>2</sup> Pass Clase Bfl-s1 ≥8kW/m <sup>2</sup> Conforme Klasse Bfl-s1 ≥8kW/m <sup>2</sup> bestanden
Chemical Resistance Resistencia a los productos químicos Chemikalieneinwirkung**		EN 423	Good Buena beständig
Castor Chair Abrasion Huellas de sillas de ruedas Stuhlrollenbeanspruchung		EN 425	Pass Conforme geeignet
Under floor heating Calefacción por el suelo Fußbodenheizung		EN 12667	Suitable Apto geeignet
Electrical Behaviours Características eléctricas Elektrisches Verhalten		EN 1815	≤ 2kV Antistatic ≤ 2kV Antiestáticas ≤ 2kV antistatisch
VOC Emissions Emisiones de VOC VOC Emissionen		pEN 15052 Section 01350 AgBB/DIBt	Low/Pass/Approved Baja/Conforme/aprobado gering/geeignet/zugelassen

\*\* Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance. This product does not contain phthalate plasticisers.

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates.