



altro
transflor

the future is safer with altro



2mm



2.5mm

Altro Transflor Met™ 20/25

Flooring Type Tipo de pavimento Belagsart		EN13845	Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag
Slip Resistance Resistencia al deslizamiento Rutschsicherheit		TRRL DIN 51130 BAM	≥36 low potential for slip R10 Extremely slip resistant
Thickness Espesor total Gesamtdicke		EN 428	2mm / 0.08" 2.5mm / 0.10"
Flexibility Flexibilidad Flexibilität		EN 435	Pass Conforme geeignet
Weight Peso Flächengewicht		EN 430	2.7kg / m ² / 4.98lbs / yd ² 3.2kg / m ² / 5.87lbs / yd ²
Roll Dimensions Dimensiones del rollo Rollenabmessungen		EN 426	2m x 20m - 40m ² 6.58' x 65.62'
Light Fastness Resistencia a la luz Lichtechtheit		EN 20105-B02	>6
Sound Insulation Aislamiento acústico Trittschall		DIN 52210	7dB (2mm only)
Wear Resistance Abrasión Verschleißverhalten		EN13845 Annex D	<10% Particles lost over 50,000 cycles <10% de las partículas perdidas en 50,000 ciclos <10% Partikelverlust bei 50.000 Umdrehungen
Indentation Punzonamiento Resteindruck		EN 433	< 0.1mm < 0.004"
Fire Performance Reacción al fuego Brandverhalten		BS 6853 NFP 92-501 NFF 16-101 ASTM E648 ASTM E662 DIN 5510	Category Ib M1 F4 Class 1 <450 DMC SF3
Chemical Resistance* Resistencia a los productos químicos Chemikalieneinwirkung		EN 423	Good Buena beständig
Castor Chair Abrasion Huellas de sillas de ruedas Stuhlrollenbeanspruchung		EN 425	Pass Conforme geeignet
Dimensional Stability Estabilidad dimensional Formstabilität		EN 434	≤0.4%