




















the future is safer with altro

altro
transflor

Technical Data Sheet Altro Transflor Timbersafe™ II

Product Description	Altro Timbersafe™ II is a 2 mm. decorative, flexible, directional heterogeneous PVC safety flooring with true wood-look effect. It features detailed wood graining and gives a jointed wooden floorboard effect. It contains aluminium oxide granules on the surface for slip-resistance and durability.		
Backing	Polyester Cellulose		
Support Reinforcement	Polyester cellulose glass fibre reinforced scrim		
Colours	3		
Flooring Type Tipo de pavimento Belagsart		EN 13845/ A STM F1303	Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag
Slip Resistance Resistencia al deslizamiento Rutschsicherheit		TRRL EN 13845 EN 13893 DIN 51130 ASTM D2047	> 36 Esf DS R10 >0.6
Thickness Espesor Total Gesamtdicke		EN 428	2 mm / 0.08"
Wear Layer Capa de uso Nutzschicht		EN 429	0.8mm / 0.031"
Flexibility Flexibilidad Flexibilität		EN 435 ASTM F1303	Pass Conforme bestanden
Weight Peso Flaechengewicht		EN 430	2.6 kg/m ² 4.8lb/sy ²
Roll Dimensions Dimensiones del rollos Rollenabmessungen		EN 426	2m x 20m - 40m ² 66' x 6.6'
Light Fastness Resistencia a la luz Lichtechtheit		EN 20105-B02 ASTM F1515	>6
Sound Insulation Aislamiento acústico Trittschal		ISO 140-8	3dB
Wear Resistance Abrasión Verschleißverhalten		ASTM C501	<10% particles lost over 50000 Cycles <10% de las partículas perdidas en 50.000 ciclos < 10% Partikel wurden über 50000 Umdrehungen verloren
Indentation Punzonamiento Resteindruck		EN433 ASTM F970	< 0.10mm
Fire Performance Reacción al fuego Brandverhalten		EN ISO 9239-1 EC 95/28 FMVSS302/CMVSS302 BS 6853 ASTM E648	8kW/m ² Approved/Aprobado/zugelassen Pass/Conforme/geeignet Category II Class 1 / Clase 1 / Klasse 1
Chemical Resistance Resistencia a los productos químicos Chemikalieneinwirkung		EN 423	Good Buena beständig
Castor Chair Abrasion Huellas de sillas de ruedas Stuhllöcherbeanspruchung		EN 425	Pass Conforme geeignet
Dimensional Stability Estabilidad dimensional Formstabilität		EN 434	≤0.4%
Electrical Behaviours Características eléctricas Elektrisches Verhalten		EN1815	< 2kV Antistatic < 2kV Antiestáticas < 2kV antistatisch
VOC Emissions Emisiones de VOC VOC Emissionen		prEN 15052 Section 01350 AgBB/DiBt	Low/Pass/Approved Baja/Conforme/Aprobado gering/geeignet/zugelassen

For recommended cleaning methods and installation advice, please visit www.altrotransflor.com