



the future is safer with altro

CI/SfB reference  
(43) T (U47)

March 2009

## High Performance hygienic PVCu wall cladding systems, ceiling systems and doorsets

recommended cleaning methods

Altro Whiterock Digiclad™

MARCH 2009

### Manual - weekly

- |  |   |
|--|---|
| <p>1. Wash with water or dilute soap/detergent solutions. Follow the manufacturer's dilution instructions. Use</p> | <p>a soft cloth only. <b>Do not use abrasive cleaners, pads or wire wool.</b></p> |
|--|---|

### Sterilisation and pressure cleaning

- |   |  |
|---|--|
| <p>1. Sterilisation solutions (supplied by others) may be used following the manufacturer's instructions</p> <p>2. Pressure cleaning with hot water lance may be carried out with the pressure nozzle a minimum of 600mm (approx 2 feet) from the wall surface.</p> | <p>N.B Observe maximum temperature of 60°C on all Altro Whiterock™ products.</p> |
|---|--|

### Heavy or stubborn stains

1. Clean heavily soiled areas with AltroClean™ 44 cleaner or equivalent alkaline cleaner

### Dusty environments

1. To reduce static charge after cleaning, apply Antistatic Solution A809 to all surfaces when dry

### Caution

- |  |   |
|--|---|
| <p>Altro Whiterock Chameleon™ has a high gloss finish and will mark if cleaners incorporating abrasive</p> | <p>agents or solutions are used. If unsure please contact Altro Technical on the number indicated below</p> |
|--|---|

Failure to maintain Altro Whiterock™ in accordance with recommended procedure can affect the performance of the product. Further information is available from Altro Walls. Please ensure you have the health and safety

data sheet for any cleaner you intend to use. In the event of any queries our Technical Services Department will be pleased to advise you.

tel: 01502 561364 fax: 01502 588848

Email: walls@altro.com

## Tips for Successful Maintenance of Altro Whiterock Digiclad™

- 1. Develop a regular cleaning programme suited to the usage and traffic of the area** – Heavily trafficked or highly visible areas, or locations with rigorous hygiene requirements, need to be cleaned more than areas which are seldom used, or where appearance is less important. A weekly cleaning programme is the minimum recommended.
- 2. Use recommended cleaning chemicals** – Use only recommended cleaning liquids, their equivalents or sterilising solutions in the correct concentration. Do not mix cleaning chemicals together, and always follow the manufacturer's instructions
- 3. Remove scuff marks and heavy soiling regularly** – Marks and soiling should be removed more than the maintenance programme, e.g. daily. Never use abrasive pads or cleaners.
- 4. Hot water lances can cause damage** – Use with care and never closer than 600mm or above maximum temperature recommendations.

High quality cleaning chemicals ensure efficient maintenance and represent only a small proportion of maintenance costs. The following suppliers offer excellent products:

### Cleaning agents and polishes

**Altro** Tel: 0870 240 8855; Fax: 0870 240 8866  
E-mail: sales@altro.com

**British Nova Works Ltd** Tel: 0208 574 6531;  
Fax: 0208 571 7572

**CSA** Tel: 01954 251573; Fax: 01954 251 931;  
E-mail: csaeagle@fsbdial.co.uk

**Diversey Lever Ltd** Tel: 01604 405311;  
Fax: 01604 406809

**Hako Clean Midlands** Tel: 01788 823535;  
Fax: 01788 823969; E-mail: sales@hako.co.uk

**Premier Products** Tel: 01242 243421;  
Fax: 01242 528445;  
E-mail: premier@premierproducts.co.uk

**Prochem Europe Ltd** Tel: 0208 974 1515;  
Fax: 0208 974 1511; E-mail: sales@prochem.co.uk

**SC Johnson** Tel: 01276 63456; Fax: 01276 852308

**3M PLC** Tel: 0161 236 8500; Fax: 0161 237 6136

HIGH PERFORMANCE HYGIENIC PVC  
WALL CLADDING SYSTEMS, CEILING  
SYSTEMS AND DOORSETS  
RECOMMENDED CLEANING METHODS

for further information or technical advice

tel: **01502 561364** fax: **01502 588848**

e-mail [walls@altro.com](mailto:walls@altro.com) or visit [www.altro.com](http://www.altro.com)