

Altro Walkway™ 20/VM20, Altro Walkway Plus™ 20/VM20 Plus

A 2mm homogeneous, slip-resistant, resilient safety floor. It is a dense and impermeable PVC floor with an Altro Easyclean Maxis PUR™ surface and an integral bacteriostat to ensure hygiene and a permanent anti-bacterial performance. www.altro.com

Un pavimento de seguridad, antideslizante de 2 mm de espesor y homogéneo. Es un pavimento de PVC denso e impermeable con tratamiento Altro Easyclean Maxis PUR™ en superficie y agente bacteriostático en toda la masa, asegurando la higiene y un permanente comportamiento antibacterias. www.altroscandess.es






















Ein homogener 2.0 mm, rutschhemmender, elastischer Bodenbelag. Die dichte und wasserundurchlässige Altro Easyclean Maxis PUR™ Oberfläche mit integriertem Biozid sorgt für eine hygienische und permanent antibakterielle Eigenschaft. www.altro.de

Altro XpressLay™, Altro XpressLay Plus™

The world's first ever, adhesive-free safety floor offers you unrivalled sustainability credentials, eliminating the need for glue. www.altro.com

El primer suelo de seguridad del mundo sin adhesivos ofrece una de las mejores credenciales en términos de sostenibilidad al haber eliminado la necesidad de pegamento. www.altroscandess.es

Der weltweit erste, lose verlegbare Sicherheitsbelag mit nachhaltigen Vorteilen. www.altro.de

Colours Colores Farben	42 (1 VM20 SD)				
Flooring Type Tipo de pavimento Belagsart	 	EN 13845/ EN 13553	Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag		
Classification for use Areas de uso Einsatzbereiche	 	EN 685	34 & 43 34 y 43 34 & 43		
Slip Resistance Resistencia al deslizamiento Rutschsicherheit*	 	TRRL EN 13845 EN 13893 DIN 51130	≥ 36 ESf DS R10		
Thickness Espesor Total Gesamtdicke		EN 428	VM20 2mm XpressLay 2.2mm		
Wear Layer Capa de uso Nutzschicht		EN 429	VM20 2mm XpressLay 0.8mm		
Flexibility Flexibilidad Flexibilität		EN 435	Pass Conforme bestanden		
Weight Peso Flächengewicht		EN 430	VM20 2.4 kg/m ² XpressLay 2.6 kg/m ²		
Roll Dimensions Dimensiones del rollo Rollenabmessungen	 	EN 426	2.0m x 20.00m - 40m ²		
Light Fastness Resistencia a la luz Lichtechtheit		EN 20105-B02	≥6		
Sound Insulation Aislamiento acústico Trittschal		ISO 140-8	VM20 5 dB XpressLay 7 dB		
Wear Resistance Abrasión Verschleißverhalten		EN13845	≤10% particles lost over 50000 Cycles ≤10% de las partículas perdidas en 50.000 ciclos ≤10% Partikel werden über 50000 Umdrehungen verloren		
Indentation Punzonamiento Resteindruck		EN 433	≤ 0.10mm		
Fire Performance Reacción al fuego Brandverhalten	 Bfl-s1	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥8kW/m ² Pass Clase Bfl-s1 ≥8kW/m ² Conforme Klasse Bfl-s1 ≥8kW/m ² , bestanden		
Chemical Resistance Resistencia a los productos químicos Chemikalieneinwirkung**		EN 423	Good Buena beständig		
Castor Chair Abrasion Huellas de sillas de ruedas Stuhlrollenbeanspruchung		EN 425	Pass Conforme geeignet		
Under floor heating Calefacción por el suelo Fußbodenheizung		EN 12667	Suitable Apto geeignet		
Electrical Behaviours Características eléctricas Elektrisches Verhalten		EN 1815	EN 1081	≤ 2kV Antistatic ≤ 2kV Antiestáticas ≤ 2kV antistatisch	≤10 ⁹ Ω (VM20SD)

** Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance. This product has never contained phthalate plasticisers.

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates.